



Cenník platný od 1.5.2018 :

| Poloautomat | vstupné napätie | Rozsah zvr. prúdu | zaťažovateľ 100% | zaťaž. 60% | prúd /zaťaž. | stupne regulácie | Kladka v stroji | drôt | oddelený podávač | meranie U2 / I2 | štvor-kladka | 2T- 4T | časovanie | chlad horáka | € bez DPH |
|---------------------------|---------------------------|-------------------|-----------------------------|----------------------|--|---------------------|------------------|---------------------|------------------|-----------------|----------------------------|---------------------|-------------------------|--------------------------|-------------------|
| Compact 154 auto | 1 x 230 V | 30 - 150 A | 70 | 90 | 150/15 | 6 | 0,6 - 0,8 | 0,6 - 0,8 | nie | nie | nie | nie | nie | nie | 559,00 € |
| Compact 2295 | 3 x 400 V | 30 - 210 A | 145 | 180 | 210/25 | 10 | 0,8 - 1,0 | 0,6 - 1,0 | nie | nie | nie | nie | nie | nie | 579,00 € |
| Compact 269 | 3 x 400 V | 30 - 260 A | 190 | 240 | 260/35 | 12 | 0,8 - 1,0 | 0,6 - 1,0 | nie | nie | na objed. | áno | áno | nie | 799,00 € |
| Compact 269 N | 3 x 400 V | 30 - 260 A | 190 | 240 | 260/35 | 12 | 0,8 - 1,0 | 0,6 - 1,0 | nie | áno | na objed. | áno | áno | nie | 859,00 € |
| Compact 329 | 3 x 400 V | 30 - 280 A | 210 | 250 | 280/30 | 12 | 0,8 - 1,0 | 0,6 - 1,2 | nie | nie | na objed. | áno | áno | nie | 899,00 € |
| Compact 329 N | 3 x 400 V | 30 - 280 A | 210 | 250 | 280/30 | 12 | 0,8 - 1,0 | 0,6 - 1,2 | nie | áno | na objed. | áno | áno | nie | 959,00 € |
| Compact 418 N | 3 x 400 V | 40 - 420 A | 290 | 320 | 420/35 | 40 | 1,0 - 1,2 | 0,6 - 1,2 | nie | áno | áno | áno | áno | nie | 1 390,00 € |
| Compact 428 WN | 3 x 400 V | 40 - 420 A | 290 | 320 | 420/35 | 40 | 1,0 - 1,2 | 0,8 - 1,6 | nie | áno | áno | áno | áno | áno | 1 890,00 € |
| Compact 428 RSWN | 3 x 400 V | 40 - 420 A | 290 | 320 | 420/35 | 40 | 1,0 - 1,2 | 0,8 - 1,6 | áno | áno | áno | áno | áno | áno | 2 190,00 € |
| Compact 508 WN | 3 x 400 V | 40 - 510 A | 350 | 420 | 510/35 | 40 | 1,0 - 1,2 | 0,8 - 1,6 | nie | áno | áno | áno | áno | áno | 2 290,00 € |
| Compact 508 RSWN | 3 x 400 V | 40 - 510 A | 350 | 420 | 510/35 | 40 | 1,0 - 1,2 | 0,8 - 1,6 | áno | áno | áno | áno | áno | áno | 2 590,00 € |
| Chladiaca jednotka | U1 | I1 | Prietok chlad. média | Pracovný tlak | Chladiace médium | Poisťky | | | | | | | | | |
| CU 609 | 1 x 230 V | 1,5 A | 1,7 lit. / min | 2,5 bar | zmes 4 lit. destilovanej vody a 1 lit. nemrznúcej kvapaliny | 2,5 AT | | | | | | | | | |
| Plazma | vstupné napätie I2 | I1 max | rezacie prúdy | zaťaž. 100% | zaťaž. 100% | prúd /zaťaž. | U20 max | kvalitný rez | možný rez | vinutie | poč.stup. regulácie | Tlak vzduchu | Množstvo vzduchu | Poisťky v prívode | |
| PC 40 - 80 | 3 x 400 V | 32 A | 40A / 80 A | 40A | x | 80A / 35% | 320 V | 15 mm | 25 mm | Cu | 2 | 0,5 Mpa | 210 lit. | 32 AT | 1 649,00 € |
| PC 120 | 3 x 400 V | 62 A | 50A/100A/120A | 50A | 100A | 120A / 60% | 320 V | 25 mm | 45 mm | Cu | 3 | 0,55 Mpa | 210 lit. | 63 AT | 2 790,00 € |

